

APPLICATION

The DynaEnergetics Modular Drop Bar is designed to be released at the surface to initiate the mechanical actuated firing heads in well with up to 40° deviation. The new modular design offers greater flexibility by simply removing one section if needed. The brass indent can be used to determine if the drop bar has reached the firing head should indication of initiation at the surface be undetermined.

Fishing Neck O.D. = 25.4mm / 1.00"

RECOMMENDATIONS

Change brass indent after each run #2316744.

Do not use in wells with deviation above 40°.


SELECTION CHART

Type	Part No.	O.D.	Length	Width	Dimensions
Modular Drop Bar Nose	2329327	31.75mm / 1.25"	177.8mm / 7 in.	1kg	177.8mm x 31.75mm
Modular Fishing Neck	2329328	31.75mm / 1.25"	152.4mm / 6 in.	.49kg	152.4mm x 31.75mm
Modular Drop Bar Body	2329112	31.75mm / 1.25"	1524mm / 5ft	9.43kg	1524mm x 31.75mm
Set Screw 10-32 x 0.19	2329337	N/A	N/A	N/A	N/A
Brass Indent	2316744	N/A	N/A	N/A	N/A

Note: Product condition must be monitored, inspected and maintained regularly to ensure proper service in accordance with DynaEnergetics guideline. Failure to do so may result in personal injury and/or property damage. For questions please contact your DynaEnergetics representative.